

Nuvite

Chemical Compounds Corporation

Product Bulletin
#233D

"products of the future that you can use today"

213 Freeman Street, Brooklyn, New York 11222 (800) 394-8351 (718) 383-8351
Fax: (718) 383-0008 On the web: www.nuvitechemical.com

NuGlaze with **PFS*** Super Paint Glosser & UV Protectant, with *PolyFluoro Sealant - for Paint in New or Excellent Condition

Nuvite introduces NuGlaze with PFS* super paint treatment to maintain a super high gloss "show quality" finish for paint in new or excellent condition. The exclusive *PolyFluoro Sealant gives a hard shine surface that resists environmental effects to maintain the gloss and color against the effects of airborne chemicals and ultraviolet radiation. NuGlaze with PFS* can also be used as a final step for maximum protection for the surface gloss and color after using Nuvite NuPol or NuPower II drywash cleaner/polishes.

With regular NuGlaze with PFS* use, a surface barrier is maintained that will resist dirt staining and makes the surface easy to clean. NuGlaze with PFS* is simple to use and avoids complicated setups and does not require special application/buffing equipment.

Nuvite's research has produced a breakthrough - a polyfluoro compound that will actually adhere to the paint at normal temperatures, unlike current popular coatings that require extreme temperatures to allow them to adhere to a surface. Nuvite NuGlaze with PFS* is a technologically advanced paint treatment, and the best thing you can do to maintain and protect your near-new or "new-condition" paint.

NuGlaze with **PFS***

- Adds a Hard Shine PolyFluoro Sealant Gloss Surface on Painted Surfaces in Good to Excellent Condition
- Seals Surface and Leaves a Protective Coating Against U/V and Atmospheric Corrosion/Salt Spray/Pollution
- Can be Used as a "Final Step" After Drywash With Nuvite NuPol or NuPower II
- Easy and Fast Application Without Power Tools or Special Setups
- Safe to All Aircraft Components, and Preserves and Protects Substrate
- Easy Application in All Climates

** PolyFluoro Sealant*

Bonnie Johnson & Linda Peconne
Cessna 172 - Air Race Classic



Charlie Gerety '37 Chevy



Dennis Spiegel '46 Ercoupe



NuGlaze

with **PFS***

**Super Paint Glosser
& UV Protectant, with
PolyFluoro Sealant
- for Paint in New
or Excellent
Condition**

Specifications:

| | |
|-------------------|---------------------------|
| Appearance: | -reddish tan liquid |
| Odor: | -mild |
| pH | -10.6-10.8 @ 25 degrees C |
| Solubility: | -dispersible in water |
| Specific Gravity: | -0.961 @ 25 degrees C |

Availability:

1 & 5 Gallon or 15, 20, 30 and 55 Gallon Drums
* PolyFluoro Sealant

Effect on Aircraft Materials:

Nuvite NuGlaze with PFS* conforms to the requirements of

- Douglas CSD #1
 - Boeing D6-17487
 - AMS 1650
- for safety to bare and clad 2024, 7075, 2524 aluminum, cadmium plated steel, mild steel, high-strength steel, Plexiglas, and paint.

Health and Safety:

Nuvite NuGlaze with PFS* is not environmentally restricted. Users should use standard safety precautions, such as wearing gloves and eye protection along with any other standard safety procedures. Refer to Material Safety Data Sheet for further information.


Directions For Use: *(NuGlaze with PFS* is intended for new condition, clean surfaces. If paint has any oxidation or needs surface cleaning, Nuvite recommends the use of an appropriate drywash paint restoration with Nuvite NuPol or a drywash cleaning with NuPower II cleaner/polish prior to NuGlaze with PFS* application.)*

For Clean, Near-New or Excellent Condition Surfaces: Apply NuGlaze with PFS* "as-is" to clean, smooth cotton towel or flannel detailing cloth and spread over a small enough area to be continuously worked without drying in the working area. Do not allow wet material to dry or to form a white haze on the surface during application procedure. Work material continuously and evenly onto surface and continue until material appears to be gone, then move to next area. Allow treated area to cure (usually no more than 5-20 minutes depending on humidity conditions). Final buff to shine with clean, dry, flannel detailing cloth (turn cloth frequently - lifting frequently will reposition fibers). Deep, very high gloss is possible with excellent paint.

For Normal or Lightly Soiled or Slightly "Aged" Surface Conditions: Prepare surface with Nuvite NuPower II drywash surface cleaner prior to application of NuGlaze with PFS*. Use NuPower II "as is" by hand, or mophead to small areas at a time (4 to 8 Sq. Ft.). Agitate area evenly with wet material. Allow to fully dry. Buff off by hand with clean, dry towel or with clean, dry mophead. Follow with application of NuGlaze with PFS* above.

For Heavily Soiled or Dulled Surface Conditions: For grease, oil, hydraulic oil buildup, or dulled paint gloss, it is recommended that a full surface restoration & cleaning with Nuvite NuPol cleaner be utilized prior to the use of NuPower II or NuGlaze with PFS* then proceed as above, depending upon paint surface condition.

Contact Nuvite representatives for further information and assistance, if required.



NUVITE CHEMICAL COMPOUNDS

C O R P O R A T I O N

213 FREEMAN STREET, BROOKLYN, NEW YORK 11222

Phone (800)394-8351 Fax (718)383-0008

www.nuvitechemical.com