



Product Bulletin
#2236B

"products of the future that you can use today"

213 Freeman Street, Brooklyn, New York 11222 (800) 394-8351 (718) 383-8351
Fax: (718) 383-0008 On the web: www.nuvitechemical.com

NuPOL SS

Drywash w/
H/D Cleaner
Paint Restorer
U/V Protectant



Nuvite NuPol SS is the high-power drywash cleaner & finish restorer for those really tough situations –baked-on carbon exhaust trails, surface staining, dull, dirt-catching oxidized paint –anywhere you need to perform “magic”! Nuvite NuPol SS is easy to use –just wipe or mop on with spun cotton scrub pad, agitate to a thin layer, let dry. When you wipe off the dry haze you will see a clean, shiny and U/V-protected paint surface! No water, power tools to set up or mess—use it anywhere. Nuvite’s NuPol SS can beat the toughest paint appearance problems, and when used with other Nuvite paint care products, gives you the easiest and best paint care system at the same time!

NuPol SS

- Heavy-Duty Drywash Cleaning
- Restores Shine and Color on Oxidized Paint on All Vehicles
- Easy Wipe On, Let Dry, Wipe Off to a Clean, Bright Surface.
- Safe to All Paints (not for clearcoats)
- Restores a Beautiful Gloss Appearance with an Effective Ultraviolet Protectant Coating on Both Painted and Metal Surfaces
- Easy Application in All Climates
- Preserves and Protects Substrate From Further Oxidation and Intensifies Color on Oxidized Paint Surfaces
- Offers Superior Cleaning Results and Protection With Fewer Man-Hours

NuPol SS

**Drywash w/
H/D Cleaner
Paint Restorer
U/V Protectant**

Specifications:

Appearance: -lt. tan, semi-viscous liquid
Odor: -mild
pH: -10.6-10.8 @ 25 degrees C
Solubility: -dispersible in water
Specific Gravity: -0.961 @ 25 degrees C

Availability:

1 & 5 Gallon or 15, 20, 30 and 55 Gallon Drums

Effect on Materials:

Nuvite NuPol SS conforms to SAE standards and requirements of

- AMS 1650
 - Boeing D6-17487
 - Douglas CSD #1
- for safety to bare and clad 2024, 7075, 2524 aluminum, cadmium plated steel, mild steel, high-strength steel, Plexiglas, and paint.

Health and Safety:


Nuvite NuPol SS is not environmentally restricted. Users should use standard safety precautions, such as wearing gloves and eye protection along with any other standard safety procedures. Refer to Material Safety Data Sheet for further information.

Directions For Use:

For Normal or Seriously Soiled Surface Conditions: Apply NuPol SS "as is" by hand, spun cotton pad, mophead or working quickly and lightly with slow speed orbital buffer to small areas at a time. Agitate area evenly with wet material to a thin layer. Increased agitation will help cleaning/deoxidation action. Allow to fully dry (usually no more than 10-15 minutes). Remove by polishing off by hand with a fluff buff with a clean cotton mophead, dry terry towel or similar to shine. For maximum shine and finish protection, follow with Nuvite PowerPol II and GlazPFS.

For Heavily Soiled or Severely Dull Surface Conditions: For grease, oil, hydraulic oil buildup, it is recommended that the area be wiped down or wet washed with Nuvite CitriCut or SS 9-3 degreasing cleaners prior to the use of NuPol SS to allow product to work without serious contamination, then proceed as above. Severely Dull paint may require two or more applications with NuPol SS. Contact Nuvite representatives for further information and assistance.

When using Nuvite materials, please refer to the appropriate procedures and recommendations for use and equipment, or consult with your Nuvite representatives for further information and demonstrations.



NUVITE CHEMICAL COMPOUNDS

C O R P O R A T I O N

213 FREEMAN STREET, BROOKLYN, NEW YORK 11222

Phone (800)394-8351 Fax (718)383-0008

www.nuvitechemical.com