

213 Freeman Street, Brooklyn, New York 11222 (800) 394-8351 (718) 383-8351
Fax: (718) 383-0008 On the web: www.nuvitechemical.com

Extractor

Low Foam
Carpet & Upholstery
Soil Extraction
Machine Fluid



Nuvite Extractor is a professional-grade suction-type soil extraction machine cleaning fluid. Its deep cleaning action makes short work of cleaning both carpeting and heavy upholstery fabrics, and, it keeps machine fouling down due to its low foaming characteristic. The formulation includes color brighteners and a mild, fresh aroma without heavy perfumes. Additionally, Nuvite Extractor helps keep your extraction equipment clean and makes cleanup easy. When you meet those tough cleaning needs in industrial and commercial buildings, or in aircraft, RV, marine, auto and truck applications, you can't do better than Nuvite Extractor. Also works great with the popular small extraction machines and scrubbers for home upkeep use. Supplied in concentrate (1-2 ounces per gallon of water.)

Extractor Professional Carpet & Upholstery Cleaning Machine Fluid

- Penetrates ground in dirt and organics
- Deep cleaning, low foaming action leaves no soapy or sticky residue
- Has color brighteners and mild aroma
- Non-toxic, Biodegradable –safe and pleasant for users and environment
- Safe to plastics, rubber and all metals
- Non-flammable/non-combustible and non-corrosive to all metals
- Hard water stable, cold water efficient
- Supplied in convenient concentrate for dilution with tap water (1-2 oz./gallon)

Extractor

Low Foam
Carpet & Upholstery
Soil Extraction
Machine Fluid

Specifications:

Appearance:	- clear, green liquid
Flash Point	- none
Odor:	- mild
pH	- 9.0 to 9.5 @ 25 degrees C
Solubility:	- infinite in water
Specific Gravity:	- 1.032 @ 25 degrees C

Availability:

Quart, 1 & 5 Gallon or 55 Gallon Drums

Effect on Aircraft Materials:

Nuvite Extractor conforms to the requirements of

- Douglas CSD #1 • Boeing D6-17487 •

for safety to bare and clad 2024, 7075, 2524 aluminum, cadmium plated steel, mild steel, high-strength steel, Plexiglas, and paint.


Health and Safety:

Nuvite Extractor is not environmentally restricted. Users should use standard safety precautions, such as wearing gloves and eye protection along with any other standard safety procedures. Refer to Material Safety Data Sheet for further information.

Directions For Use:

Carpet Extraction Machine Application: Follow instructions on machine, using 1 to 2 ounces of Nuvite Extractor per gallon of water to be used, depending upon soiling of carpet or upholstery. Test affect on lightweight upholstery fabrics in unobtrusive area before using over all. Lukewarm water may be used. Carpet Extraction: do not allow carpet backing to be soaked.

Carpet Pre Spot Cleaning: Use Nuvite PCS Professional Carpet Spotter concentrate diluted 1:4 to 1:8 with water. Test carpet for color fastness in inconspicuous area. After determining that carpet is color fast, spray terry towel to dampen cloth, then apply to soiled spots. Soak out as much soil as possible into dry terry towel. If soil spot persists after soaking with towel, spray PCS directly on spot and use soft brush to agitate up and down, then side to side. Reapply dry terry towel to soak out agitated residue. Repeat as needed. Follow with full carpet extraction using Nuvite Extractor as described above prior to pre spotted areas drying. Severely soiled carpeting may benefit from repeat extraction. Contact Nuvite representatives for further information/assistance.



NUVITE CHEMICAL COMPOUNDS

C O R P O R A T I O N

213 FREEMAN STREET, BROOKLYN, NEW YORK 11222

Phone (800)394-8351 Fax (718)383-0008

www.nuvitechemical.com